

PROJECT

TYPE

MEMO

ORDERING CODE BREAKDOWN

LED GRIDLITE (GEN 2)
SITE LIGHT FIXTURE

MAIN FEATURES

- Designed with a die-cast, aluminum alloy housing for optimal thermal performance and exceptional corrosion resistance
- Delivering up to 170 lumens per watt
- 3,000- to 20,000 lumen packages (20-160W)
- Extended site arm offers universal mounting, allowing for retrofit without drilling into existing poles
- All mounting options allow for multiple fixture installations at 90°
- TGIC polyester super durable powder coating with superior gloss, color retention, and weather resistance
- 0-10V dimming standard; DALI-2 dimming option available
- BAA Compliance available; *Consult factory to confirm specific fixture code is compliant if this is a requirement*
- Designed and assembled in U.S.A.!



FIXTURE	LUMENS	BEAM SPREAD	CRI ⁶	CCT	VOLTAGE	CONTROLS	SURGE	PHOTOCELL RECEPTACLE	FINISH	MOUNTING	FIXTURE OPTIONS	FIELD OPTIONS
GL1	3H : 3,000 lm; 21W	2RM : Type II Roadway Medium	7 : 70 CRI	30 : 3000K	STD : 120-277V	10 ⁵ : 0-10V	1PS : 10kV 5kA, 120-277V	00 : None	SBZ : Bronze (RAL8019)	WP ⁴ : Wall Pack	ZT1 ⁵ : 0-10V Z Ambient Light Control	PCL-01 : 120-277V Photocell
	4H : 4,000 lm; 25W	3RM : Type III Roadway Medium	8 : 80 CRI	40 : 4000K	HVL : 277-480V	DA : DALI-2 D4i	2PS : *20kV 10kA, 120-277V	70 ³ : 7-pin	SGY : Gray (RAL7038)		ZT3 ⁵ : 0-10V Z IR + Ambient Light Control	PCL-02 : 120-277V Photocell
	5H : 5,000 lm; 32W	3AM : Type III Area Medium		50 : 5000K	SEM ³ : 120-277V w/ 10W EM (3H-16H only)		2PH : *20kV 10kA, 277-480V	0Z ³⁵ : Z receptacle	SWH : White (RAL9003)		ZT4 ⁵ : 0-10V Z Occupancy + IR + Ambient Light Control	PCL-03 : 347-480V Photocell
	6H : 6,000 lm; 42W	4WS ¹² : Type IV Wide Short						S0 : Synapse compatible 7-pin	SBK : Black (RAL9017)		ZT5 ⁵ : 0-10V Z Casambi Bluetooth Mesh Node	PCL-04 : 347-480V Photocell (Midnight Dim)
	7H : 7,000 lm; 52W	5QS : Type V Square Short						0B : Zhaga Book 10 compatible			HSS ¹ : House-side Shield	PCL-05 : 120-277V Photocell (Midnight Dim)
	8H : 8,000 lm; 60W	5QM : Type V Square Medium									FSS : Front-side Shield	ENL-SC1 : Shorting Cap
	9H : 9,000 lm; 65W										CSS : Cul-de-Sac Shield	SMCB ⁴ : Wall Pack Surface Mount Conduit Box
	11H : 11,000 lm; 80W										SS ¹² : Scoop Shield	ERP ⁷ : Extended Site Arm Round Pole Adapter
	12H : 12,000 lm; 89W										CC* : Coastal Construction	FRP ⁸ : Fixed Arm Round Pole Adapter
	13H : 13,000 lm; 101W											
	14H : 14,000 lm; 112W											
	16H : 15,000 lm; 131W											
	16P : 16,000 lm; 123W											
	18P : 18,000 lm; 143W											
	20P : 20,000 lm; 164W											

Notes: Consult factory to verify BAA compliant products
¹HSS not compatible with 4WS optics, instead use SS.
²SS for use with 4WS optic only
³SEM not compatible with 7-pin (70) or Z receptacle (0Z); Available with lumen packages 3H-16H only

*Consult factory for lead time and availability
⁴SMCB for use with Wall Pack (WP)
⁵ZT1 - ZT5 options only available with 0-10V controls (10) and Z receptacle (0Z)
⁶80 or 90 CRI, + additional CCTs available upon request

PROJECT

TYPE

LED GRIDLITE (GEN 2)
SITE LIGHT FIXTURE

FINISH

- TGIC polyester super-durable powder coating with superior gloss, color retention and weather resistance
- Standard finishes provided at 3 mil nominal thickness, salt-spray-tested to 3,000 hours as per ASTM B117

MOUNTING

- Extended site arm offers universal mounting, allowing for retrofit without drilling into existing poles
- Options allow for multiple fixture installations at 90°
- Wall-mount and round pole adapters are available for extended and fixed site arms

CONSTRUCTION

- Die-cast, aluminum alloy housing for optimal thermal performance and exceptional corrosion resistance
- 100% recycled aluminum

WARRANTY

- 5-year warranty

ELECTRICAL

- 120-277V Standard; 277-480V option available
- PF>0.9, THD<20%
- Parallel surge protection: enhanced 10kV standard, extreme 20kV optional (ANSI C136.2-2015)
- For series surge protection, consult factory
- Rated for operation -40°C to 40°C
- For 50°C option, consult factory

OPTICS + PERFORMANCE

- Up to 170 lumens per watt
- 3,000- to 20,000 lumen packages (20-160W)
- 5 customized distributions available
 - Type II Roadway Medium (Coefficient of Utilization: 0.793)
 - Type III Roadway Medium (Coefficient of Utilization: 0.852)
 - Type IV Wide Short (Coefficient of Utilization: 0.840)
 - Type V Square Short
 - Type V Square Medium
- Multiple shielding options available

CONTROLS

- 0-10V dimming standard; DALI-2 option available
- Receptacle options:
 - ANSI C136.41 3-pin
 - ANSI C136.41 7-pin (for DALI-2 or 0-10 V dimming)
 - Zhaga Book 18 (for next generation ambient light/motion sensing)
 - Zhaga Book 10 (for use with Autani smart controls)

LISTINGS

- IP66-rated optical and electrical chambers
- 3G Vibration-rated (ANSI C136.31)
- cULus Listed for wet locations
- IDA Dark Sky listed with ≤3000K (Site Arm, Horizontal Tenon)
- Zhaga D4i listed
- ANSI C136.15 labeling available
- BAA Compliance available; *Consult factory to confirm specific fixture code is compliant if this is a requirement*
- **Designed and assembled in U.S.A.**

LUMEN AMBIENT TEMPERATURE (LAT) MULTIPLIERS

Ambient Temperature		Lumen Multiplier
Celsius	Fahrenheit	
0°C	32°F	1.02
10°C	50°F	1.01
25°C	77°F	1.00
40°C	104°F	0.99
50°C	122°F	0.97

TM-21 LUMEN MAINTENANCE PROJECTION

Calculated by utilizing the LED manufacturer’s LM80 test data in conjunction with third party verified in-situ LED drive current and LED temperature data. Use data below to determine light loss factors.

50,000 hrs	60,000 hrs	100,000 hrs
99.67%	99.49%	98.77%

WEIGHTS + EPA INFORMATION

Mounting Type	Weight		
	Below 9H	11H to 16H	16P to 20P
Extended Site Arm (ES)	14.33 lbs.	16.02 lbs.	16.48 lbs.
Horizontal Tenon (HT)	12.76 lbs.	14.45 lbs.	14.91 lbs.
Knuckle Mount (KM)	12.77 lbs.	14.46 lbs.	14.92 lbs.
Wall Pack (WP)	13.19 lbs.	14.88 lbs.	15.34 lbs.
Wall Pack (WP) with SMCB	15.40 lbs.	17.09 lbs.	17.55 lbs.
Fixed Arm (FA)	14.92 lbs.	16.61 lbs.	16.48 lbs.

• Data below includes luminaire and integrated mounting option. Additional tenons, arms and brackets are not included.

Mounting Type	Tilt	Single	2 at 90°	2 at 180°	2 at 120°	3 at 90°	3 at 120°	4 at 90°	2 Side-by-Side
Extended Site Arm (ES)	n/a	0.67 sq. ft.	1.17 sq. ft.	1.34 sq. ft.	1.49 sq. ft.	1.84 sq. ft.	1.99 sq. ft.	1.84 sq. ft.	1.00 sq. ft.
Extended Site Arm (ES) with Round Pole Adapter (ERP)	n/a	0.72 sq. ft.	1.22 sq. ft.	1.43 sq. ft.	1.54 sq. ft.	1.93 sq. ft.	2.04 sq. ft.	1.93 sq. ft.	1.00 sq. ft.
Horizontal Tenon (HT)	n/a	0.48 sq. ft.	0.78 sq. ft.	0.96 sq. ft.	0.98 sq. ft.	1.26 sq. ft.	1.28 sq. ft.	1.26 sq. ft.	0.60 sq. ft.
Knuckle Mount (KM) (7.5° increments)	90° (horizontal)	0.56 sq. ft.	0.97 sq. ft.	1.12 sq. ft.	1.13 sq. ft.	1.54 sq. ft.	1.54 sq. ft.	1.54 sq. ft.	0.83 sq. ft.
	60°	0.56 sq. ft.	1.34 sq. ft.	1.12 sq. ft.	1.70 sq. ft.	1.91 sq. ft.	2.49 sq. ft.	1.91 sq. ft.	1.56 sq. ft.
	45°	0.56 sq. ft.	1.56 sq. ft.	1.12 sq. ft.	2.04 sq. ft.	2.12 sq. ft.	3.04 sq. ft.	2.12 sq. ft.	2.00 sq. ft.
	30°	0.56 sq. ft.	1.72 sq. ft.	1.12 sq. ft.	2.33 sq. ft.	2.28 sq. ft.	3.48 sq. ft.	2.28 sq. ft.	2.31 sq. ft.
	0° (vertical)	0.56 sq. ft.	1.83 sq. ft.	1.12 sq. ft.	2.50 sq. ft.	2.39 sq. ft.	3.77 sq. ft.	2.39 sq. ft.	2.54 sq. ft.
Fixed Arm (FA)	n/a	0.59 sq. ft.	0.97 sq. ft.	1.18 sq. ft.	1.25 sq. ft.	1.56 sq. ft.	1.63 sq. ft.	1.56 sq. ft.	0.77 sq. ft.





PROJECT

TYPE

LED GRIDLITE (GEN 2) SITE LIGHT FIXTURE



Fixed Arm (FA)

- Simple and easy installation





Extended Site Arm (ES)

- Universal mount adapter
- Allows for retrofit without drilling into existing poles





Horizontal Tenon (HT)

- Mounts to maximum 2 3/4" O.D. tenon





Knuckle (KM)



- Mounts to maximum 3" O.D. tenon
- Adjustable at 7.5° increments
- Not recommended to angle luminaire past 0° (vertical); maintain downward angle



Wall Pack (WP)




Wall Pack (WP) - SMCB (field-installed option)




PHOTOMETRIC DISTRIBUTION


TYPE II ROADWAY MEDIUM (2RM)




TYPE III ROADWAY MEDIUM (3RM)




TYPE III AREA MEDIUM (3AM)




TYPE IV WIDE SHORT (4WS)



TYPE V SQUARE SHORT (5QS)




TYPE V SQUARE MEDIUM (5QM)



SHIELD ACCESSORY DETAILS


HOUSE SIDE SHIELD (HSS)

- Flat-black, injection molded plastic resin
- Tool-less, clip-on discrete shield
- Blocks light behind the fixture




CUL-DE-SAC SHIELD (CSS)

- Flat-black, injection molded plastic resin
- Tool-less, clip-on discrete shield
- Blocks light to left and right of the fixture



FRONT SIDE SHIELD (FSS)

- Flat-black, injection molded plastic resin
- Tool-less, clip-on discrete shield
- Blocks light in front of the fixture.



SCOOP SHIELD (SS)

- Flat-black, injection-molded plastic resin
- Tool-less, clip-on discrete shield
- Blocks light behind the fixture (4WS only)



CONTROLS

0-10 V ZHAGA OPTIONS

- ZT1: Ambient Light Control
- ZT3: IR + Ambient Light Control
- ZT4: Occupancy + IR + Ambient Light Control
- ZT5: 0-10V Zhaga Casambi BLE + ALC



PHOTOCELL OPTIONS

- PCL01: 120-277V Photocell (640J, IP65); Blue
- PCL02: 120-277V Photocell (1280J, IP66); Blue
- PCL03: 347-480V Photocell (1280J, IP66); Yellow
- PCL04: 50% Midnight Dimming, 347-480V Photocell (1280J, IP65); Brown
- PCL05: 50% Midnight Dimming, 120-277V Photocell (1280J, IP65); Brown



PROJECT

TYPE

LED GRIDLITE (GEN 2)
SITE LIGHT FIXTURE

Performance Package	Wattage Label	Drive Current	Color Temp. (CCT)	Input Power (Watts)	TYPE II ROADWAY MED (2RM) AT 70 CRI			TYPE III ROADWAY MED (3RM) AT 70 CRI			TYPE III AREA MED (3AM) AT 70 CRI			TYPE IV WIDE SHORT (4WS) AT 70 CRI			TYPE V SQUARE SHORT (5QS) AT 70 CRI			TYPE V SQUARE MED (5QM) AT 70 CRI		
					Lumens	Efficacy (lm/W)	BUG Rating	Lumens	Efficacy (lm/W)	BUG Rating	Lumens	Efficacy (lm/W)	BUG Rating	Lumens	Efficacy (lm/W)	BUG Rating	Lumens	Efficacy (lm/W)	BUG Rating	Lumens	Efficacy (lm/W)	BUG Rating
3H	20	250mA	5000K	21.0	3,590	171	1 0 1	3,601	171	1 0 1	3,493	166	1 0 2	3,418	162	1 0 1	3,605	171	2 0 1	3,470	165	2 0 1
			4000K		3,555	169	1 0 1	3,565	170	1 0 1	3,458	164	1 0 2	3,384	161	1 0 1	3,569	170	2 0 1	3,436	163	2 0 1
			3000K		3,412	162	1 0 1	3,423	163	1 0 1	3,320	158	1 0 2	3,248	154	1 0 1	3,426	163	2 0 1	3,298	157	2 0 1
4H	30	300mA	5000K	25.4	4,291	169	1 0 1	4,305	169	1 0 1	4,175	164	1 0 2	4,085	161	1 0 1	4,309	169	2 0 1	4,148	163	2 0 1
			4000K		4,249	167	1 0 1	4,262	168	1 0 1	4,134	162	1 0 2	4,045	159	1 0 1	4,266	168	2 0 1	4,107	161	2 0 1
			3000K		4,079	160	1 0 1	4,091	161	1 0 1	3,969	156	1 0 2	3,883	153	1 0 1	4,096	161	2 0 1	3,943	155	2 0 1
5H	30	375mA	5000K	32.6	5,357	164	1 0 1	5,373	165	1 0 1	5,212	160	1 0 2	5,099	156	1 0 2	5,379	165	2 0 1	5,178	159	3 0 1
			4000K		5,304	163	1 0 1	5,320	163	1 0 1	5,160	158	1 0 2	5,049	155	1 0 1	5,325	163	2 0 1	5,127	157	3 0 1
			3000K		5,092	156	1 0 1	5,107	157	1 0 1	4,954	152	1 0 2	4,847	149	1 0 1	5,112	157	2 0 1	4,922	151	3 0 1
6H	40	483mA	5000K	42.7	6,775	159	1 0 1	6,796	159	1 0 2	6,592	154	1 0 2	6,450	151	1 0 2	6,803	159	3 0 1	6,549	153	3 0 1
			4000K		6,708	157	1 0 1	6,729	158	1 0 1	6,527	153	1 0 2	6,386	149	1 0 2	6,736	158	3 0 1	6,484	152	3 0 1
			3000K		6,440	151	1 0 1	6,459	151	1 0 1	6,266	147	1 0 2	6,131	144	1 0 2	6,466	151	3 0 1	6,225	146	3 0 1
7H	50	585mA	5000K	52.5	8,009	152	1 0 2	8,033	153	1 0 2	7,792	148	1 0 2	7,624	145	1 0 2	8,042	153	3 0 2	7,742	147	3 0 2
			4000K		7,930	151	1 0 2	7,954	151	1 0 2	7,715	147	1 0 2	7,549	144	1 0 2	7,962	152	3 0 2	7,665	146	3 0 2
			3000K		7,612	145	1 0 2	7,635	145	1 0 2	7,406	141	1 0 2	7,247	138	1 0 2	7,643	146	3 0 1	7,358	140	3 0 2
8H	60	672mA	5000K	61.2	9,024	147	1 0 2	9,051	148	1 0 2	8,779	143	1 0 2	8,590	140	1 0 2	9,061	148	3 0 2	8,722	143	3 0 2
			4000K		8,934	146	1 0 2	8,961	146	1 0 2	8,693	142	1 0 2	8,505	139	1 0 2	8,971	147	3 0 2	8,636	141	3 0 2
			3000K		8,577	140	1 0 2	8,603	141	1 0 2	8,345	136	1 0 2	8,165	133	1 0 2	8,612	141	3 0 2	8,291	136	3 0 2
9H	70	725mA	5000K	66.2	9,565	145	2 0 2	9,594	145	1 0 2	9,306	141	1 0 2	9,106	138	1 0 2	9,604	145	3 0 2	9,246	140	3 0 2
			4000K		9,470	143	2 0 2	9,499	144	1 0 2	9,214	139	1 0 2	9,016	136	1 0 2	9,509	144	3 0 2	9,154	138	3 0 2
			3000K		9,092	137	1 0 2	9,119	138	1 0 2	8,846	134	1 0 2	8,655	131	1 0 2	9,129	138	3 0 2	8,788	133	3 0 2
11H	80	924mA	5000K	81.5	11,692	143	2 0 2	11,728	144	1 0 2	11,376	140	1 0 2	11,131	137	2 0 2	11,740	144	3 0 2	11,302	139	4 0 2
			4000K		11,577	142	2 0 2	11,612	142	1 0 2	11,264	138	1 0 2	11,021	135	2 0 2	11,624	143	3 0 2	11,190	137	4 0 2
			3000K		11,114	136	2 0 2	11,147	137	1 0 2	10,813	133	1 0 2	10,580	130	1 0 2	11,159	137	3 0 2	10,743	132	4 0 2
12H	90	1029mA	5000K	90.8	12,641	139	2 0 2	12,679	140	1 0 2	12,299	136	1 0 2	12,034	133	2 0 2	12,693	140	3 0 2	12,219	135	4 0 2
			4000K		12,516	138	2 0 2	12,554	138	1 0 2	12,177	134	1 0 2	11,915	131	2 0 2	12,567	138	3 0 2	12,098	133	4 0 2
			3000K		12,015	132	2 0 2	12,052	133	1 0 2	11,690	129	1 0 2	11,438	126	2 0 2	12,064	133	3 0 2	11,614	128	4 0 2
13H	100	1134mA	5000K	100.6	13,601	135	2 0 2	13,642	136	2 0 2	13,233	132	1 0 2	12,948	129	2 0 2	13,657	136	3 0 2	13,147	131	4 0 2
			4000K		13,466	134	2 0 2	13,507	134	2 0 2	13,102	130	1 0 2	12,820	127	2 0 2	13,522	134	3 0 2	13,017	129	4 0 2
			3000K		12,928	129	2 0 2	12,967	129	1 0 2	12,578	125	1 0 2	12,307	122	2 0 2	12,981	129	3 0 2	12,496	124	4 0 2
14H	110	1281mA	5000K	114.6	14,840	129	2 0 2	14,885	130	2 0 2	14,438	126	1 0 2	14,127	123	2 0 3	14,901	130	4 0 2	14,345	125	4 0 2
			4000K		14,693	128	2 0 2	14,738	129	2 0 2	14,295	125	1 0 2	13,987	122	2 0 2	14,753	129	4 0 2	14,203	124	4 0 2
			3000K		14,105	123	2 0 2	14,148	123	2 0 2	13,724	120	1 0 2	13,428	117	2 0 2	14,163	124	3 0 2	13,634	119	4 0 2
16H	130	1449mA	5000K	130.8	16,101	123	2 0 2	16,150	124	2 0 2	15,665	120	1 0 2	15,328	117	2 0 3	16,167	124	4 0 2	15,563	119	4 0 2
			4000K		15,941	122	2 0 2	15,990	122	2 0 2	15,510	119	1 0 2	15,176	116	2 0 3	16,007	122	4 0 2	15,409	118	4 0 2
			3000K		15,304	117	2 0 2	15,350	117	2 0 2	14,890	114	1 0 2	14,569	111	2 0 3	15,366	118	4 0 2	14,793	113	4 0 2
16P	120	1365mA	5000K	122.9	16,387	133	3 0 3	16,434	134	2 0 2	15,756	128	2 0 2	15,202	124	2 0 2	16,278	132	2 0 2	15,389	125	4 0 2
			4000K		16,225	132	3 0 3	16,271	132	2 0 2	15,600	127	2 0 2	15,051	122	2 0 2	16,117	131	2 0 2	15,237	124	4 0 2
			3000K		15,576	127	3 0 3	15,620	127	2 0 2	14,976	122	2 0 2	14,449	118	2 0 2	15,472	126	2 0 2	14,628	119	4 0 2
18P	140	1608mA	5000K	143.2	18,151	127	3 0 3	18,203	127	2 0 2	17,452	122	3 0 3	16,838	118	3 0 3	18,030	126	3 0 3	17,046	119	4 0 2
			4000K		17,972	125	3 0 3	18,023	126	2 0 2	17,280	121	3 0 3	16,672	116	3 0 3	17,852	125	3 0 3	16,877	118	4 0 2
			3000K		17,253	120	3 0 3	17,302	121	2 0 2	16,588	116	2 0 3	16,005	112	2 0 3	17,138	120	2 0 2	16,202	113	4 0 2
20P	160	1709mA	5000K	164.4	19,771	120	3 0 3	19,827	121	2 0 3	19,010	116	3 0 3	18,341	112	3 0 3	19,639	119	3 0 3	18,567	113	4 0 2
			4000K		19,575	119	3 0 3	19,631	119	2 0 2	18,822	114	3 0 3	18,159	110	3 0 3	19,445	118	3 0 3	18,383	112	4 0 2
			3000K		18,792	114	3 0 3	18,846	115	2 0 2	18,069	110	3 0 3	17,433	106	3 0 3	18,667	114	3 0 3	17,648	107	4 0 2