

PROJECT _____ TYPE _____

MEMO _____

ORDERING CODE BREAKDOWN

MAIN FEATURES

- Designed with a die-cast, 100% recycled aluminum alloy housing for optimal thermal performance and exceptional corrosion resistance
- Delivering up to 151 lumens per watt
- 18,000- to 30,000 lumen packages (131-238W)
- Extended site arm offers universal mounting, allowing for retrofit without drilling into existing poles
- All mounting allows for multiple installations at 90°
- TGIC polyester super durable powder coating with superior gloss, color retention, and weather resistance
- 0-10V dimming standard; DALI-2 dimming option available
- BAA/BABA Compliance available; *Consult factory to confirm specific fixture code is compliant if this is a requirement*
- **Designed and assembled in U.S.A.!**



Extended Site Arm

EPA: 0.69 sq. ft.

WEIGHT: 21.45 - 23.87 lbs.



FIXTURE	LUMENS	BEAM SPREAD	CRI	CCT	VOLTAGE CONTROLS	SURGE	PHOTOCELL RECEPTACLE	FINISH	MOUNTING	FIXTURE OPTIONS	ADAPTER OPTIONS	FIELD OPTIONS	
GL2	18H: 18,000 lm; 131W	2RM : Type II Roadway Medium	7: 70 CRI	30 : 3000K	STD : 120-277V	10 : 0-10V	1PS: 10kV 5kA, 120-277V	00 : None	SBZ : Bronze (RAL8019)	ES : Extended Site Arm	ZT1 : 0-10V Z Ambient Light Control	RP : Site Arm Round Pole Adapter	SOL28 HSS : House-side Shield
	20H: 20,000 lm; 150W	3RM : Type III Roadway Medium	8: 80 CRI	40 : 4000K	HVL : 277-480V	DA : DALI-2 D4i	2PS: *20kV 10kA, 120-277V	70 : 7-pin	SGY : Gray (RAL7038)	HT : Horizontal Tenon	ZT3 : 0-10V Z IR + Ambient Light Control	SMCB : Wall Pack Surface Mount Conduit Box	SOL28 FSS : Front-side Shield
	23H: 23,000 lm; 180W	3AM : Type III Area Medium		50 : 5000K			2PH: *20kV 10kA, 277-480V	0Z : Z receptacle	SWH : White (RAL9003)	KM : 3" OD Knuckle Mount	ZT4 : 0-10V Z Occupancy + IR + Ambient Light Control	ERP : Extended Site Arm Round Pole Adapter	SOL28 CSS : Cul-de-Sac Shield
	26H: 26,000 lm; 212W	4WS : Type IV Wide Short						7Z : 7-pin + Z	SBK : Black (RAL9017)	WP : Wall Pack	ZT5 : 0-10V Z Casambi Bluetooth		SOL28 SS : Scoop Shield
	28H: 29,000 lm; 238W	5QS : Type V Square Short							MBZ : *Marine Bronze				PCL-01 : 120-277V Photocell
		5QM : Type V Square Medium						MGY : *Marine Grey					PCL-02 : 120-277V Photocell
								MWH : *Marine White					PCL-03 : 347-480V Photocell
								MBK : *Marine Black					PCL-04 : 347-480V Photocell (Midnight Dim)
													PCL-05 : 120-277V Photocell (Midnight Dim)
													ENL-SC1 : Shorting Cap

Notes: †Consult factory to verify BAA/BABA compliant products. Additional CRIs and/or CCTs available upon request HSS not compatible with 4WS optics, instead use SS.

*Consult factory for lead time and availability. HVL unavailable with ZT1, ZT3, ZT4 and ZT5 photocell receptacles. ZT1 - ZT5 options only available with 10 : 0-10V Dimming

PROJECT _____

TYPE _____

FINISH

- TGIC polyester super-durable powder coating with superior gloss, color retention and weather resistance
- Standard finishes provided at 3 mil nominal thickness, salt-spray-tested to 3,000 hours as per ASTM B117
- For marine-grade finish, consult factory. Provided at 5 mil nominal thickness, salt-spray-tested to 4,000 hours as per ASTM B117

MOUNTING

- Extended site arm offers universal mounting, allowing for retrofit without drilling into existing poles
- Options allow for multiple fixture installations at 90°
- Wall-mount and round pole adapters are available for extended site arm

CONSTRUCTION

- Die-cast, aluminum alloy housing for optimal thermal performance and exceptional corrosion resistance
- 100% recycled aluminum

ELECTRICAL

- 120-277 V Standard; 277-480 V option available
- PF>0.9, THD<20%
- Parallel surge protection: enhanced 10kV standard, extreme 20kV optional (ANSI C136.2-2015)
- For series surge protection, consult factory
- Rated for operation -40°C to 40°C
- For 50°C option, consult factory

OPTICS + PERFORMANCE

- Up to 151 lumens per watt
- 18,000- to 30,000 lumen packages (131-238W)
- 5 customized distributions available
 - Type II Roadway Medium (Coefficient of Utilization: 0.793)
 - Type III Roadway Medium (Coefficient of Utilization: 0.852)
 - Type IV Wide Short (Coefficient of Utilization: 0.840)
 - Type V Square Short
- Type V Square Medium
- Multiple shielding options available

CONTROLS

- 0-10 V dimming standard; DALI-2 option available
- Receptacle options:
 - ANSI C136.41 3-pin
 - ANSI C136.41 7-pin (for DALI-2 or 0-10 V dimming)
 - Zhaga Book 18 (for next generation ambient light/motion sensing)

LISTINGS




- IP66-rated optical and electrical chambers
- 3G Vibration-rated (ANSI C136.31)
- cULus Listed for wet locations
- IDA Dark Sky listed with $\leq 3000K$ (Site Arm, Horizontal Tenon)
- Zhaga D4i listed
- ANSI C136.15 labeling available
- BAA/BABA Compliance available; *Consult factory to confirm specific fixture code is compliant if this is a requirement*
- **Designed and assembled in U.S.A.**

WARRANTY



- 5-year warranty

EXTENDED SITE ARM (ES)

- Universal mount adapter
- Allows for retrofit without drilling into existing poles





WALL PACK (WP)





WALL PACK WITH SURFACE MOUNT CONDUIT BOX (WP-SMBC)

- Field installed option






HORIZONTAL TENON (HT)

- Mounts to maximum 2 3/4" O.D. tenon



KNUCKLE MOUNT (KM)

- Mounts to maximum 3" O.D. tenon
- Adjustable at 7.5° increments
- Not recommended to angle luminaire past 0° (vertical); maintain downward angle



PROJECT _____

TYPE _____

LUMEN AMBIENT TEMPERATURE (LAT) MULTIPLIERS

Ambient Temperature		Lumen Multiplier
Celsius	Fahrenheit	
0°C	32°F	1.02
10°C	50°F	1.01
25°C	77°F	1.00
40°C	104°F	0.99
50°C	122°F	0.97

TM-21 LUMEN MAINTENANCE PROJECTION

▪ Calculated by utilizing the LED manufacturer's LM80 test data in conjunction with third-party-verified in situ LED drive current and LED temperature data. Use data below to determine light-loss factors.

Performance Package	50,000 Hrs	60,000 Hrs	100,000 Hrs
18H to 23H	99.67%	99.49%	98.77%
26H	98.95%	98.62%	97.30%
28H	95.73%	94.83%	91.34%




ELECTRICAL LOAD

Performance Package	Input Power	Current (Amps) per Input Voltage					
		120 Vac	208 Vac	240 Vac	277 Vac	347 Vac	480 Vac
18H	131.4 W	1.10	0.63	0.55	0.47	0.38	0.27
20H	149.6 W	1.25	0.72	0.62	0.54	0.43	0.31
23H	180.3 W	1.50	0.87	0.75	0.65	0.52	0.38
26H	212.4 W	1.77	0.83	0.72	0.63	0.50	0.36
28H	238.1 W	1.98	1.14	0.99	0.86	0.69	0.50

WEIGHTS + EPA INFORMATION


Mounting Type	EPA	Weight
Extended Site Arm (ES)	0.69 sq. ft.	23.31 lbs.
Extended Site Arm with Round Pole Adapter (ES-RP)	0.73 sq. ft.	23.87 lbs.
Horizontal Tenon (HT)	0.54 sq. ft.	21.45 lbs.
Knuckle Mount (KM)	0.61 sq. ft.	21.45 lbs.

▪ Data below includes luminaire and integrated mounting option. Additional tenons, arms and brackets are not included.


Mounting Type	Tilt	Single	2 at 90°	2 at 180°	2 at 120°	3 at 90°	3 at 120°	4 at 90°	2 Side-by-Side
									
Extended Site Arm (ES)	n/a	0.69 sq. ft.	1.10 sq. ft.	1.38 sq. ft.	1.46 sq. ft.	1.79 sq. ft.	1.87 sq. ft.	1.79 sq. ft.	0.82 sq. ft.
Extended Site Arm (ES) with Round Pole Adapter (ERP)	n/a	0.73 sq. ft.	1.14 sq. ft.	1.46 sq. ft.	1.50 sq. ft.	1.87 sq. ft.	1.91 sq. ft.	1.87 sq. ft.	0.82 sq. ft.
Horizontal Tenon (HT)	n/a	0.54 sq. ft.	0.78 sq. ft.	1.08 sq. ft.	1.02 sq. ft.	1.32 sq. ft.	1.26 sq. ft.	1.32 sq. ft.	0.54 sq. ft.
Knuckle Mount (KM) (7.5° increments)	90° (horizontal)	0.61 sq. ft.	0.95 sq. ft.	1.22 sq. ft.	1.14 sq. ft.	1.56 sq. ft.	1.48 sq. ft.	1.56 sq. ft.	0.68 sq. ft.
	60°	0.61 sq. ft.	1.46 sq. ft.	1.22 sq. ft.	1.68 sq. ft.	2.07 sq. ft.	2.53 sq. ft.	2.07 sq. ft.	1.70 sq. ft.
	45°	0.61 sq. ft.	1.72 sq. ft.	1.22 sq. ft.	1.94 sq. ft.	2.33 sq. ft.	3.05 sq. ft.	2.33 sq. ft.	2.22 sq. ft.
	30°	0.61 sq. ft.	1.91 sq. ft.	1.22 sq. ft.	2.14 sq. ft.	2.52 sq. ft.	3.44 sq. ft.	2.52 sq. ft.	2.60 sq. ft.
	0° (vertical)	0.61 sq. ft.	2.11 sq. ft.	1.22 sq. ft.	2.66 sq. ft.	2.72 sq. ft.	4.16 sq. ft.	2.72 sq. ft.	3.00 sq. ft.

PHOTOMETRIC DISTRIBUTION


TYPE II ROADWAY MEDIUM (2RM)




TYPE III ROADWAY MEDIUM (3RM)




TYPE IV WIDE SHORT (4WS)



TYPE V SQUARE SHORT (5QS)



TYPE V SQUARE MEDIUM (5QM)



SHIELD ACCESSORY DETAILS


HOUSE SIDE SHIELD (HSS)

- Flat-black, injection molded plastic resin
- Tool-less, clip-on discrete shield
- Blocks light behind the fixture




CUL-DE-SAC SHIELD (CSS)

- Flat-black, injection molded plastic resin
- Tool-less, clip-on discrete shield
- Blocks light to left and right of the fixture



FRONT SIDE SHIELD (FSS)

- Flat-black, injection molded plastic resin
- Tool-less, clip-on discrete shield
- Blocks light in front of the fixture.



SCOOP SHIELD (SS)

- Flat-black, injection-molded plastic resin
- Tool-less, clip-on discrete shield
- Blocks light behind the fixture (4WS only)



CONTROLS


0-10 V ZHAGA OPTIONS

- ZT1: Ambient Light Control
- ZT3: IR + Ambient Light Control
- ZT4: Occupancy + IR + Ambient Light Control
- ZT5: 0-10V Zhaga Casambi BLE + ALC



PHOTOCELL OPTIONS

- PCL01: 120-277V Photocell (640J, IP65); Blue
- PCL02: 120-277V Photocell (1280J, IP66); Blue
- PCL03: 347-480V Photocell (1280J, IP66); Yellow
- PCL04: 50% Midnight Dimming, 347-480V Photocell (1280J, IP65); Brown
- PCL05: 50% Midnight Dimming, 120-277V Photocell (1280J, IP65); Brown



PROJECT _____

TYPE _____

LED GRIDLITE (GEN 2) SITE LIGHT FIXTURE

Performance Package	Wattage Label	Drive Current	Color Temp. (CCT)	Input Power (Watts)	TYPE II ROADWAY MED (2RM) AT 70 CRI			TYPE III ROADWAY MED (3RM) AT 70 CRI			TYPE III AREA MED (3AM) AT 70 CRI			TYPE IV WIDE SHORT (4WS) AT 70 CRI			TYPE V SQUARE SHORT (5QS) AT 70 CRI			TYPE V SQUARE MED (5QM) AT 70 CRI		
					Lumens	Efficacy (lm/W)	BUG Rating	Lumens	Efficacy (lm/W)	BUG Rating	Lumens	Efficacy (lm/W)	BUG Rating	Lumens	Efficacy (lm/W)	BUG Rating	Lumens	Efficacy (lm/W)	BUG Rating	Lumens	Efficacy (lm/W)	BUG Rating
18H	120	776mA	5000K	131.4	19,657	150	3 0 3	19,838	151	2 0 2	19,019	145	2 0 3	18,826	143	2 0 3	19,851	151	4 0 2	18,860	144	4 0 2
			4000K		19,392	148	3 0 3	19,570	149	2 0 2	18,763	143	2 0 3	18,572	141	2 0 3	19,584	149	4 0 2	18,606	142	4 0 2
			3000K		17,855	136	3 0 3	18,019	137	2 0 2	17,275	131	2 0 2	17,100	130	2 0 3	18,031	137	4 0 2	17,131	130	4 0 2
20H	140	854mA	5000K	149.6	21,761	145	3 0 3	21,962	147	2 0 3	21,055	141	3 0 3	20,841	139	3 0 3	21,976	147	4 0 2	20,879	140	5 0 3
			4000K		21,468	144	3 0 3	21,666	145	2 0 3	20,772	139	3 0 3	20,561	137	2 0 3	21,680	145	4 0 2	20,598	138	4 0 3
			3000K		19,767	132	3 0 3	19,948	133	2 0 2	19,125	128	2 0 3	18,931	127	2 0 3	19,962	133	4 0 2	18,965	127	4 0 2
23H	120	1022mA	5000K	180.3	25,007	139	3 0 3	25,237	140	3 0 3	24,196	134	3 0 3	23,950	133	3 0 4	25,254	140	4 0 2	23,994	133	5 0 3
			4000K		24,671	137	3 0 3	24,898	138	3 0 3	23,870	132	3 0 3	23,628	131	3 0 3	24,914	138	4 0 2	23,670	131	5 0 3
			3000K		22,715	126	3 0 3	22,924	127	3 0 3	21,978	122	3 0 3	21,755	121	3 0 3	22,939	127	4 0 2	21,794	121	5 0 3
26H	140	1189mA	5000K	212.4	27,957	132	3 0 3	28,214	133	3 0 3	27,049	127	3 0 4	26,775	126	3 0 4	28,233	133	4 0 2	26,823	126	5 0 3
			4000K		27,580	130	3 0 3	27,834	131	3 0 3	26,685	126	3 0 4	26,414	124	3 0 4	27,853	131	4 0 2	26,462	125	5 0 3
			3000K		25,394	120	3 0 3	25,628	121	3 0 3	24,570	116	3 0 3	24,320	115	3 0 4	25,645	121	4 0 2	24,364	115	5 0 3
28H	160	1323mA	5000K	238.1	29,930	126	3 0 3	30,205	127	3 0 3	28,958	122	3 0 4	28,664	120	3 0 4	30,225	127	5 0 3	28,716	121	5 0 3
			4000K		29,527	124	3 0 3	29,798	125	3 0 3	28,568	120	3 0 4	28,278	119	3 0 4	29,818	125	5 0 3	28,329	119	5 0 3
			3000K		27,186	114	3 0 3	27,436	115	3 0 3	26,304	110	3 0 4	26,037	109	3 0 4	27,455	115	4 0 2	26,084	110	5 0 3

POLE INFORMATION

• Solais offers a full line of aluminum and steel poles, brackets and accessories for your installation. For more information, consult factory.

SQUARE STRAIGHT

- 8- to 39-ft. height options

ROUND STRAIGHT

- 8- to 35-ft. height options

SQUARE TAPERED

- 20- to 50-ft. height options

ROUND TAPERED

- 8- to 39-ft. height options
- 45- to 70-ft. telescoping height options

HINGED TAPERED

- 20- to 39-ft. height options

