

RDC + RDE

REACH-IN DOOR RETROFIT CENTER + END PIECE LUMINAIRES

PROJECT _____

TYPE _____

SPECIFICATION _____

- Class 2 low voltage fixture
- 50,000 Hours (L70)
- UL Listed
- NSF certified
- RoHs-compliant
- IP66 wet location rated
- DesignLights Consortium® Certification (DLC)
- Contain no lead or mercury
- Dimming based on power supply
- Single-piece extrusion
- Shatter-resistant housing
- Motion sensor option
- Wiring box accessory available
- Ideal for reach-in freezer and coolers with an external power supply



Ordering Information

Example: RDC48/35K/1600/BK/BB-UB

Fixture	Length	Throw S - Standard	CCT 35K 40K* 50K*	Lumens	Color BK - Black	Accessories
RDC (Center Piece)	48			1000		(blank) - Upper + lower bracket built in; 1 center bracket included CB - Additional Center Bracket WB - Wiring Box (Note: adding a wiring box increases the overall length by 1.4")
	60			1250		
	72			1350		
RDE (End Piece)	48			650		
	60			675		
	72			900		
				1050		

Note: Data below based on 4000K. Use output multipliers on right to calculate data for other color temperatures.

Fixture	Nominal Length	Lumen Output	Power (Watts)	MOL (inches)	Weight	CRI	CCT	Multiplier
RDC	48"	1000	7.5	42 3/4	10.3 oz.	>80	3500K	0.97
	60"	1250	9.3	56 1/2	11.2 oz.		4000K	1.00
		1350	10.1	69 1/2	12.0 oz.		5000K	1.00
RDE	48"	650	4.8	42 3/4	10.3 oz.			
	60"	675	5.0	56 1/2	11.2 oz.			
		900	6.5	69 1/2	12.0 oz.			
	72"	1050	7.8	69 1/2	12.0 oz.			

