

Scatto | SCCR

48V TRACK SYSTEM

ROUND SHAPE SUSPENSION

MAIN FEATURES

- Designed for surface mount or hanging suspension applications
- Designed for linear luminaires to extend past the track and trackhead adapters to sit flush
- Great for use in architectural and high-end applications
- Field-cutable for custom lengths

RATINGS + CERTIFICATIONS

- UL Certified for dry locations
- RoHS-compliant
- Designed for use with Solais® Scatto™ fixtures and components

ELECTRICAL + SAFETY

- 48V, +/- 2A
- 96W maximum load

CONSTRUCTION + FINISH

- Extruded aluminum construction standard finish in black (RAL 9005)
- Insulated extruded body in PVC
- Solid copper conductors

WARRANTY

- 3-year warranty



Ordering Information



Scatto Type + Length

- SC31-CR-4 - 4ft. Round suspension
- SC31-CR-8 - 8ft. Round suspension



SC31 Accessories

- SC-UM-TCV - Track Cover
- SC-CR-ECC - End Cap
- SC-UM-SRB - Reinforcing Bracket
- SC-UM-TCT - Conductor Cutting Tool







SC31 Connectors

- SC31-UM-EFR - End feed, Right Polarity
- SC31-UM-EFL - End feed, Left Polarity
- SC31-UM-SJC - Straight Joining Connector
- SC31-UM-SIC - Straight Isolating Connector
- SC31-UM-LFI - 'L' live feed, Inner Polarity
- SC31-UM-LFO - 'L' live feed, Outer Polarity
- SC31-UM-TOL - 'T' live feed, Outer/Left Polarity
- SC31-UM-TOR - 'T' live feed, Outer/Right Polarity
- SC31-UM-TIL - 'T' live feed, Inner/Left Polarity
- SC31-UM-TIR - 'T' live feed, Inner/Right Polarity
- SC31-UM-XFC - 'X' live feed
- SC31-UM-ACR - Adjustable Connector









Scatto Suspension






- SC-UM-TCC - Ceiling Clamp
- SC-CR-SPB - Short Pendant Bracket
- SS-UM-SEG - Side Exit Gripper
- SS-UM-SMC - Surface Mount Cable Coupler
- SS-UM-DLG - Double Looping-Gripper
- SS-UM-ACB - Barrel End Aircraft Cable, 20 ft.
- SS-UM-ACL - Loop End Aircraft Cable, 20 ft.
- SS-UM-CPC - Ceiling Cup with Ceiling Bracket



Technical drawing of a T-joint. The horizontal member has a width of 278. The vertical member has a height of 1407. The drawing shows the joint from a side perspective, with a cross-section view of the joint shown to the right.

Technical drawing of a T-shaped metal part. The top horizontal section has a width of 278. The vertical section has a height of 147. The part is shown in two views: a front view and a side view.

Scatto Suspension		
SC-UM-TCC Ceiling Clamp <i>Steel; Recommended for use with SS-U-SEG</i>		
SC-CR-SPB Short Pendant Bracket <i>Aluminum; For aircraft Cable Suspension; Recommended for use with SS-U-SEG</i>		
SS-UM-CPC Ceiling Cup <i>with ceiling bracket and screw gripper for use with cable suspension</i>		

Track Suspension Accessories		
SS-UM-TSC T-bar Seismic Suspension Clamp <i>For use where local code requires direct connection to the ceiling. Ceiling-supported clip for 15/16" T-bar</i>		
SS-UM-ACL Aircraft Cable with Loop <i>20 feet of 1/16" galvanized cable. Recommended for use with SS-UM-SEG.</i>		
SS-UM-ACB Aircraft Cable with Barrel <i>20 feet of 1/16" galvanized cable. Recommended for use with SS-UM-SEG.</i>		
SS-UM-SEG Side Cable Exit Gripper <i>For use with 3/64" or 1/16" threaded cable only. Recommended for use with SS-UM-ACL or SS-UM-ACB.</i>		
SS-UM-SMC Surface Mount Cable Coupler <i>2-part non-adjustable cable coupler. Recommended for use with SS-UM-ACB.</i>		
SS-UM-DLG Double Mechanism Looping Gripper <i>Double-ended gripper with double side cable exits for use with 3/64" or 1/16" threaded cable only.</i>	