

iDL3

LOW-MID OUTPUT INTERNATIONAL DOWNLIGHT

PROJECT _____

TYPE _____

- / 230 - 240 V only
- / 50,000 Hours (L70)
- / Driver included
- / SAA, CE and CCC Certified
- / RoHS-compliant
- / Dry location rating
- / Contain no lead or mercury
- / 90+ High CRI standard
- / Non-dimmable



Weight: TBD
Ceiling Cut-Out: \varnothing 5 1/4"





950 Lumen



Ordering Information

Example: iDL3/NF/950/1500/WH/EM

Fixture	Beam Spread	CRI + CCT	Lumen Output	Flange Color
iDL3	SP - Spot NF - Narrow Flood FL - Flood WF - Wide Flood	927 - 90 CRI, 27K 930 - 90 CRI, 30K 935 - 90 CRI, 35K 940 - 90 CRI, 40K 950 - 90 CRI, 50K	950 1500	WH - White BK - Black SV - Silver



1500 Lumen



Warranty

WARNING: Not for use in fully enclosed luminaires. Risk of electric shock. Use in an indoor, dry location only. This device is not intended for use with emergency exit fixtures or emergency exit lights. May not be compatible with all dimmers; please visit solais.com/dimming for up-to-date dimmer compatibility information.

NOTES: This device complies with Part 15 of the FCC Rule. This product may cause interference with other devices. If interference occurs, change the locations of the products involved. **Compatible on 120v systems.**